

Sleek Kiosk

Feature

15", 17" or 19" TFT LCD

Resistive, Capacitive & SAW Touch screen

Ticket or Receipt printer

Card Reader

Bluetooth, LAN connectivity

Sleek Kiosk

SK 5.0

The slim construction and compact design, **Sleek Kiosk** are used as information terminal. With the touch screen feature, browsing for information is a breeze.

Car showroom deploy **Sleek Kiosk** for customers to read the vehicle technical specification. During idle time, the kiosk will play featured video of the specific model.

In Government offices, **Sleek Kiosk** are deployed as queue ticket issuing terminal. The kiosk also double as information kiosk during idle state.

Corporate play company video and product introduction on the kiosk to keep visitors entertained while waiting at the reception.

Education Institution use the kiosk for public information, result checking, school notice terminal or web surfing.



Typical Application

- Information Kiosk
- Queue Ticket Kiosk
- Company Profile Kiosk
- Catalogue Kiosk
- School services kiosk
- Government Services Information

Accessories & Component for Kiosk

Open frame Touch screen LCD Monitor

- Touch screen - Resistive, SAW or Capacitive type
- 15", 17" or 19" TFT LCD
- Resolution – XGA or SXGA
- Sunlight readable available as optional item



Power Distribution Unit, PDU-MS4M

- Internal AC power distribution
- Metal Clad casing for industrial safety
- Built-in push button MCB for overload protection



Receipt / Queue Ticket Printer

- Thermal printer for 60, 85 & 114mm paper width
- High print quality
- Virtually maintenance free thermal printing
- Easy user, USB Interface
- Reliable system control



Bar Code Reader

- Illumination – 530 NM visible red LED
- Reading distance 5 – 100mm
- Easy user, PS/2 keyboard interface protocol



Swipe Card Reader

- Support ISO, IBM, DIN, ANSI etc
- Easy user, USB Interface



Other Sleek Kiosk Design & Form Factor



SK1.0



SK2.0



SK3.0



SK3.2



SK4.0

Overall Dimension

SK1.0 & SK1.1

- 950H x 500W x 450D mm

SK2.0

- 1,350H x 500W x 500D mm

SK3.0

- 1,450H x 550W x 450D mm

SK3.2

- 1,450H x 550W x 500D mm

